

## LOBASOL<sup>®</sup> HS Akzent 100 Oil



### Product description

Solvent-free floor oil basing on vegetable oils. The wood's structure will be fortified.

### Range of Use

Suitable to impregnate wooden floors. HS Akzent 100 Oil achieves the increased anti-slip class R10 according to BGR 181 and DIN 51130.

Suitable for toys according to DIN EN 71-3.

### Features

- 100% High solid – solvent free
- Accentuates the natural color of the wood
- High water spot resistance
- Increased slip resistance
- For normally frequentet areas application in a one day system possible

### Technical Data

<b>Article No.</b>	10601	<b>Application Rate</b>	30-60 g/m <sup>2</sup> depending on the substrates' absorbing properties.
<b>Package Size</b>	3l, 0,75l	<b>Application Tool</b>	LOBATOOL roller Microfaser 60-80, LOBATOOL stainless trowel
<b>Packing</b>	Box: 6 x 3l Pallet: 180 x 3l Box: 6 x 0,75l Pallet: 432 x 0,75l	<b>Even out</b>	LOBA Special-Pad beige
<b>Storage and Transportation</b>	Not sensitive to frost, storable for 36 months, no hazardous material according to ADR	<b>Drying Time</b>	Walk on After 12 h Slightly stressable After 24 h Fully stressable After 10 days
<b>Giscode</b>	Ö 10	<b>Thinner</b>	Do not dilute. Product is ready to use.

Store soaked cloth, pads and other tools in closed containers. Sanding dust, cloths, etc. contaminated with oil / wax must be wettened with water, stored in a lockable container or disposed fire-proofely in another way.

**Otherwise danger of self-ignition.**

### Full declaration

Refined vegetable oils (sunflower oil, wood oil, linseed oil), silicic acid, drying agents (lead-free), antioxidant (free from phenol and oxime)

# LOBASOL<sup>®</sup> HS Akzent 100 Oil

### Information on Use:

- Bring product to the temperature of (+18°C to+25°C) before use.
- Shake material well
- Regard safety regulations
- Regard climatic conditions\*
- Ventilate working area \*

\*) Regard General Information on the use LOBASOL<sup>®</sup> products

### Preparation:

Sand surface of hardwood floors technically correct. Remove sanding dust accurately (vacuum-clean). The surface must be dry and in addition free from oil, wax, silicone and old coating residues.

### Setup recommendation

#### Normal wear – trowel application

1. Apply HS Akzent 100 Oil in a constantly thin layer by using trowel
2. Exposure time of 20 minutes
3. Even out surface with a single-disc machine and LOBA Special-Pad beige
4. Apply HS Akzent 100 Oil in a constantly thin layer by using trowel
5. Exposure time of 20 minutes
6. Even out surface with a single-disc machine and LOBA Special-Pad beige

#### Normal wear – roller application

1. Apply HS Akzent 100 Oil transparent in a constantly thin layer by using a Microfaser 60/80 roller
2. Exposure time of 1 hour
3. Even out surface with a single-disc machine and LOBA Special-Pad beige

#### Heavy wear – trowel application

1. Apply HS Akzent 100 Oil in a constantly thin layer by using trowel
2. Remove all residues immediately by using a single-disc-machine with a LOBA Spezial Pad beige put underneath
3. Drying over night
4. Apply HS Akzent 100 Oil in a constantly thin layer by using trowel
5. Remove all residues immediately by using a single-disc-machine with a LOBA Spezial Pad beige put underneath

### Notice:

In the above mentioned trowel application HS Akzent 100 Wax can be used for second application instead of HS Akzent 100 Oil. Let the oil dry over-night when using HS Akzent 100 Wax afterwards, the requirements for an increased slip resistance cannot be met. Regard detailed instructions mentioned in the technical information of HS Akzent 100 Wax.

Trowel application is only possible if the floor is free of gaps, oil penetrating into open joints is not drying entirely for a long period of time. On Floors with broad joints and wood planks with beveled edges we recommend the use HS 2K ImpactOil.

### Caution!

Make sure to remove any excessive material from the floor during the equalization steps. On some exotic woods curing time can be retarded.

The general information on the use of LOBASOL<sup>®</sup> products are part of this information and must be noticed.